

09517173-030200

MOTION PICTURE INFORMATION DISPLAYING METHOD AND APPARATUS

## BACKGROUND OF THE INVENTION

The present invention relates to an image information displaying method and apparatus in which a motion picture is edited by operating icons or screen menus on a display screen by means of a GUI (Graphical User Interface).

In recent years, the enhancement of speed of computers and the improvement in functionality thereof have brought about the rapid progress of the variegation and improvement in functionality of software. The improvement in functionality of a production equipment for producing or arranging a TV broadcast program or video program has been advanced by use of a computer and an image editing program.

Particularly, in the recent program arrangement, the edition of image information using a motion picture editing apparatus with a random access information storage device (for example, a hard disk which is easy of handling and preservation and is low in cost) is made in lieu of an image editing method in which a video tape recorder is used to edit an image by repeating the quick feed and rewind depending a tape counter. The use of such a motion picture editing apparatus in combination with a computer and software improved in functionality and variegated has made the progress of more improvement in functionality of the motion picture editing apparatus. Here, the image informa-

Fig. 4 shows an example of display on a screen used for an edition processing in a motion picture editing

5 apparatus for editing a motion picture by use of a  
computer. With the use of a motion picture editing  
apparatus provided with a required edition processing  
software in a memory device, image information of a motion  
picture to be edited can be managed in a manner stored in  
10 the memory device. Reduced versions of cut images or scene  
images of a motion picture stored in the memory device are  
displayed as moving icons (M-icons) on a monitor screen to  
form a tree structure having cut images or scene images as  
its unit, thereby making it possible to perform an editing  
15 work for the motion picture. In the screen shown in Fig.  
4, reference numeral 1000 denotes an editing window,  
numeral 1010 an editing area, numeral 1020 a material area,  
numerals 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, ---  
moving icons of image materials or sources displayed in the  
20 material area 1020 (where K, M and N are natural numbers  
and  $K = N-2$  and  $M = N-1$  are satisfied), and numeral 1040 a  
tree structure which is formed by moving icons and  
represents the contents of edition of an edited motion  
picture.

25           The cut images, scene images, moving icons (M-  
icons) and so forth will now be described.

A cut image 1210 is a set of frame images obtained through one photographing by a TV camera from its

start to its end, and a representative image representing a series of frame images.

A scene image 1220 is a set of plural cut images 1210 obtained for a predetermined object of photographing.

5 A plurality of scene images 1220 may be gathered to provide a block 1230. A plurality of blocks 1230 can be gathered on the basis of a specified theme of photographing to provide or display an edited motion picture (or program) 1240 of the specified photographing theme.

10 Thus, a motion picture to be edited can be arranged as image data with a hierarchical structure (or tree structure) which may be formed by several cut images 1210 selected from among a plurality of cut images 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- as image  
15 materials in compliance with a specified theme of photographing, scene images 1220 each including the collection of a plurality of cut images 1210, blocks 1230 each including a group of selected scene images 1220, and a motion picture 1240 including the collection of blocks 1230  
20 and providing a program with a title.

This tree structure is ordered and applied with data of a series of frame numbers for a motion picture, frame numbers of images at detected cut change points, cut image numbers serially applied to cut images, and sequence  
25 numbers representing the sequence of plural cut images each forming a scene image. This data or hierarchical structure information is included in control information used in the motion picture editing apparatus.

The M-icons are GUI (Graphical User Interface) parts each having a one-to-one correspondence to a cut image, that is, a representative image representing a series of frame images obtained through one photographing  
5 from its start to its end.

The M-icon is an image for the purpose of display which has a size reduced at a required ratio. The M-icons are displayed in the case where scene images or the whole or a part of a motion picture formed by a plurality of  
10 frame images are to be viewed promptly, as required. Otherwise, the M-icons may be displayed as representative ones of cut images.

The monitor screen provides a GUI screen for displaying edition information of cut images, scene images  
15 and a tree structure representative of the state of edition which is used for the edition of a motion picture. An editor uses an input device (for example, a mouse or keyboard) to select this edition information displayed on the monitor screen, thereby making it possible to give an  
20 instruction to the motion picture editing apparatus.

Thus, with the construction in which a motion picture to be edited is stored and managed as a tree structure, the motion picture editing apparatus is enabled to arrange a program and to perform an editing work with  
25 cut images or scene images taken as units.

The screen of the motion picture editing apparatus shown in Fig. 4 can be used, as a specific example, in the case where image materials 1030-1033 of an

existing news program are used as materials of edition to prepare another news program (e.g. a digest version) newly.

In the display screen shown in Fig. 4, reference numeral 1050 denotes a group of edition function buttons for selecting various control functions used in an editing work, numeral 1051 a character (or appearing person) detecting button, numeral 1052 a tree structure forming button, numeral 1070 a slider for sliding the display contents of the editing area 1010 in a lateral direction, numeral 1080 a slider for sliding the display contents of the editing area 1010 in a longitudinal direction, numeral 1090 a slider for sliding the display contents of the material area 1020 in a longitudinal direction, numeral 1210 M-icons representative of cut images registered in the editing area 1010, numeral 1220 an M-icon representative of a scene image formed by one or plural cut images, numeral 1230 an M-icon formed one or more scene images, numeral 1240 an M-icon representative of a motion picture (or program) edited in compliance with a given theme, and numeral 810 a mouse pointer displayed on the GUI screen when a GUI operation is performed by a pointing device such as a mouse. Though the M-icon has thereon the corresponding reduced image for the purpose of display, the illustration or depiction of this reduced image will be omitted for avoiding the complexity, so long as there is no special necessity.

In Fig. 4, the tree structure 1040 formed by the M-icons in the editing area 1010 is such that one or plural

M-icons 1210 on a first hierarchical layer representing cut images selected for edition are collected to form an M-icon 1220 representative of a scene image as a second hierarchical layer on the first hierarchical layer, one or plural  
5 M-icons 1220 representing the scene images are collected to form an M-icon 1230 representative of the collection of specified scene images as a third hierarchical layer on the second hierarchical layer, and a plurality of M-icons 1230 each representing the collection of specified scene images  
10 are finally collected to form an M-icon 1240 representing a program edited in compliance with a theme.

The number of hierarchical layers in the tree structure 1040 may be arbitrary. It is of course that an upper hierarchical layer can further be provided. Since  
15 the size of the window of the editing area 1010 is limited, there may be the case where it is not possible to display the whole of the tree structure 1040 within the editing area 1010. In order to see an undisplayed portion, the slider 1070 or 1080 is operated by use of the input device  
20 to move the display contents of the editing area 1010 in a required lateral or longitudinal direction, thereby making it possible to view the whole of the tree structure 1040.

In the material area 1020, different cut images obtained by detecting cut change points for a series of  
25 motion picture materials and dividing them at the cut change points are temporarily located as image material M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- which are displayed so that it is possible to take a look

at them.

At a stage in which the editing work proceeds to the invocation of images so that M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- are generated and  
5 displayed, the M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- are displayed in the material area 1010 at a time serial sequence in the left to right direction and the up to down direction.

Also for the M-icons 1030, 1031, 1032, 1033, ---,  
10 103K, 103M, 103N, --- in the material area 1020, there may be the case where the number of the M-icons is large so that they cannot be displayed in the window of the material area 1020 at once, as in the case of the editing area 1010. In that case, the slider 1090 can be operated by use of the  
15 input device to move the display contents of the material area 1020 in the longitudinal direction, thereby making it possible to view all the M-icons.

In order to perform the edition, M-icons required for edition are selected from the material area 1020 and  
20 the tree structure forming button 1052 in the function button group 1050 is then turned on. Thereby, the selected M-icon 1030 is moved or copied into the editing area 1010. Thus, the tree structure 1040 is formed to make progress on the edition.

25 Fig. 4 shows a state in which the progress of the edition to a certain extent is attained so that the tree structure 1040 has already been formed in the editing area 1010 and the edition is then continued to further select

002020 - E212560



desired M-icons from among the M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- in the material area 1020.

The M-icon displayed in the material area 1020 or the editing area 1010 is shown as one card in the illustration of the figure. However, this is a simplified form. On the actual monitor screen, each M-icon is displayed in a form having the thickness of superimposition of frame images possessed by that M-icon.

Though the edition of the motion picture is advanced, there is less the case where image materials actually required for the arrangement of a program are all image information stored in the information storage device (cut images or a series of motion pictures read as a file of one motion picture).

Namely, there may not be the case where all the plurality of M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- displayed in the material area 1020 become necessary. Only image materials associated with some M-icons selected in accordance with an object of edition or a theme of photographing are used for a program.

Also, since it is general that a plurality of scenes are included in the image materials, a search is made so that M-icons required for edition are selected from among a multiplicity of M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, --- included in image materials or image information read from the information storage device.

The operation of the motion picture editing apparatus using the screen shown in Fig. 4 and the method

of performing the edition of a motion picture while forming a tree structure by use of M-icons have been disclosed by, for example, JP-A-10-51733.

Also, JP-A-2-184181 has disclosed an example of  
5 means for detecting change points for cut images, that is, a technique of analyzing the illuminance, sound volume, color tone or the like of a motion picture to detect a portion with a remarkable change as a change point for a cut image.

10 In order to perform the edition of a motion picture as mentioned above, it is required for an editor that an M-icon representing a cut necessary for the program should be selected from among the plurality of M-icons 1030, 1031, 1032, 1033, ---, 103K, 103M, 103N, ---  
15 displayed in the material area 1020.

One function supporting the search for the necessary M-icon is a character detecting function. The character detecting function detects an object such as a specified character or person from image materials or  
20 plural cuts or scenes. Here, this specified character, that is object is assumed as "X".

With the character detecting function, an operator selects and inputs the combination of features possessed by the object "X" so that a search for a frame  
25 conformable to those features and its pixel region is made from image materials or plural cuts or scenes (that is, images in a section subjected to detection) by use of an image recognition technique.

09517173-030600

JP-A-6-223179 has disclosed a method in which a cut containing a specified object therein is detected from a motion picture on the basis of the features of that character.

5 First, the operator designates the combination of features (for example, hair color, skin color and dress color) of a specified person or an object "X" in a series of selected M-icons (that is, a section subjected to detection where the character "X" may appear). Thereby,  
10 the motion picture editing apparatus detects an image region conformable to the designated combination of colors through an image processing so that information of the conforming image and its frame is displayed on the GUI screen.

15 When the frame containing the character "X" therein is detected, the editor confirms a cut which includes that frame. If this cut is appropriate as a part of the program material, the cut is selected and is inserted into the hierarchical structure 1040 of the  
20 editing area 1010 shown in Fig. 4.

In the conventional motion picture editing apparatus, a frame containing a specified image is detected from a motion picture but there is not provided a function of displaying information of the result of detection in a  
25 form which is comprehensible for an editor to use as information for edition. Also, the conventional motion picture editing apparatus is not capable of displaying a motion picture range having already been subjected to a

0054743.03000

processing for detection of a frame containing a specified character therein and a range having not yet been subjected to the detection processing so that they are displayed on a screen in a distinctive manner. Further, there is not  
5 provided a function of make a correction or change for the result of detection.

#### SUMMARY OF THE INVENTION

002050 030300  
10 An object of the present invention is to provide a method and apparatus in which a frame containing a specified image therein is detected from a motion picture on the basis of features possessed by the specified image and information of the result of detection is displayed on a motion picture editing screen in a form comprehensible for an editor. Another object of the present invention is  
15 to display a motion picture range having already been subjected to a processing for detection of a frame containing a specified character therein and a range having not yet been subjected to the detection processing so that they are displayed on a screen in a distinctive manner. A  
20 further object of the present invention is to provide an editing screen with a function of making a correction or change for the result of detection. The specified image to be detected in the method or apparatus of the present invention is not limited to a character or person and may  
25 include a physical solid other than a character, a scenery (or landscape) and so forth.

In an image information displaying method for the

0051773.030200

edition of a motion picture in one aspect of the present invention, representative image representing a series of frame images forming the motion picture are displayed on a screen of a display device and a hierarchical structure based on a plurality of representative images is generated on the screen through an operation using a GUI to perform the edition of the motion picture. According to the present invention, a plurality of frame images included in the representative image are subjected to an image detection processing for detecting frame images having a predetermined image recorded thereon. Information indicating the detected frame image having the predetermined image recorded thereon is displayed as a detection result displaying window on the screen. Information concerning frame images having not been subjected to the image detection processing is displayed on the detection result displaying window.

An image information displaying apparatus for the edition of a motion picture according to another aspect of the present invention comprises a display device having a screen for displaying representative images representing a series of frame images forming the motion picture, a control device for controlling image information displayed on the screen of the display device, a storage device for storing the frame images, the image information and data for managing the frame images and the image information, and an input device for inputting data into the control device. The control device includes means with which a

hierarchical structure based on a plurality of representative images is generated on the screen of the display device on the basis of data inputted by the input device and in response to an operation using a GUI, means with  
5 which a plurality of frame images included in the representative image are subjected to an image detection processing for detecting a frame image having a predetermined image recorded thereon, means with which information indicative of the detected frame image having the predetermined image recorded thereon is displayed as a detection  
10 result displaying window on the screen, and means with which information concerning frame images having not been subjected to the image detection processing is displayed on the detection result displaying window.

15           The image information displaying method for the edition of a motion picture according to the present invention can be stored in a recording medium as a program which can be read by a computer. The computer readable medium has computer readable program code means comprising  
20 means with which representative images representing a series of frame images forming the motion picture are displayed on a screen of a display device, means with which a hierarchical structure based on a plurality of representative images is generated and displayed on the screen of  
25 the display device on the basis of inputted instruction data, means with which a plurality of frame images included in the representative image are subjected to an image detection processing for detecting frame images having a

00517173-030200

predetermined image recorded thereon, means with which  
information indicative of the detected frame image having  
the predetermined image recorded thereon is displayed as a  
detection result displaying window on the screen, and means  
5 with which information concerning frame images having not  
been subjected to the image detection processing is  
displayed on the detection result displaying window.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram showing an embodiment of an  
10 IDX window in the present invention;

Fig. 2 is a diagram an example of an ID window  
for explaining the detection of character;

Fig. 3 is a block diagram showing an example of  
the construction of a motion picture editing/displaying  
15 apparatus;

Fig. 4 is a diagram showing an example of display  
on an editing window;

Fig. 5 is a diagram showing an example of an  
initial state of an IDX window in the present invention;

Fig. 6 is a diagram showing an example of display  
20 of the result of image detection on an IDX window;

Fig. 7 is a diagram showing an embodiment of an  
IDX window in the present invention;

Fig. 8 is a diagram showing an example of an  
25 editing window;

Figs. 9A, 9B and 9C are views showing that the  
result of a detection of an object is displayed on a side

00547473-030200

Fig. 10 is a diagram showing an embodiment of an IDX window in the present invention;

Figs. 12A, 12B and 12C are views showing that the result of a detection of an object is displayed on a side face of an M-icon which represents a representative image in the form of a solid figure;

Fig. 14 is a diagram showing an example of display on an ID panel;

Fig. 16 is a diagram showing an embodiment of an ID panel in the present invention;

Fig. 18 is a diagram showing an embodiment of a monitor screen on which an editing window, an ID panel and an IDX panel are simultaneously displayed;

Fig. 20 is a diagram showing an editing window



according to an embodiment of the present invention;

Fig. 21 is a diagram showing an editing window according to an embodiment of the present invention;

Fig. 22 is a diagram showing multi-window display  
5 according to an embodiment of the present invention;

Fig. 23 is a diagram showing an embodiment of an IDX panel in the present invention;

Fig. 24 is a diagram showing an ID panel according to an embodiment of the present invention;

10 Fig. 25 is a diagram showing an embodiment of a multi-window screen on which an editing window, an ID panel and an IDX panel are simultaneously displayed;

Fig. 26 is a diagram showing an embodiment in which an editing window, an ID panel and an IDX panel are  
15 simultaneously displayed;

Fig. 27 shows a flow chart showing an embodiment of a processing for making a correction for a detection effectuating domain according to the present invention;

Fig. 28 is an embodiment of an ID panel in the  
20 present invention;

Fig. 29 is a diagram showing an ID panel according to an embodiment;

Fig. 30 shows a flow chart showing an embodiment of a processing for interpolation change in selected frame  
25 according to the present invention;

Fig. 31 is a diagram showing an embodiment of an ID panel in which an interpolation change in selected frame according to the present invention is made;

00517173-030200

Fig. 32 is a diagram showing an embodiment of an ID panel in which an interpolation change in selected frame according to the present invention is made;

Fig. 33 shows a flow chart in the case where  
5 information of the result of image detection is stored into the data structures of M-icons in the lowermost layer of a hierarchical structure;

Fig. 34 shows a flow chart of a procedure for  
distinctively displaying a zone having already been  
10 subjected to image detection processing and a zone having not yet been subjected to image detection processing;

Fig. 35 shows an example of a data structure concerning a hierarchical structure for attached M-icons;

Fig. 36 shows an example of a data structure  
15 concerning a hierarchical structure for scenes;

Figs. 37A, 37B and 37C show an example of a data structure concerning a hierarchical structure for cuts;

Fig. 38 shows another example of the data structure concerning the hierarchical structure for cuts;

Fig. 39 shows a further example of the data  
20 structure concerning the hierarchical structure for cuts;

Fig. 40 shows a furthermore example of the data structure concerning the hierarchical structure for cuts;  
and

Fig. 41 shows a still further example of the data  
25 structure concerning the hierarchical structure for cuts.

00547173-030300

## DESCRIPTION OF THE EMBODIMENTS

Embodiments of a method and apparatus of the present invention will now be described in reference to the drawings.

5           Fig. 3 is a block diagram showing an example of the construction of a motion picture editing apparatus according to the present invention. Reference numeral 3010 denotes a CPU (Central Processing Unit), numeral 3020 a memory, numeral 3030 a cut change point detecting unit,  
10 numeral 3040 an image reproducing device, numeral 3050 a video interface, numeral 3060 a random access information storage device such as a magnetic disk, numeral 3070 a frame buffer, numeral 3080 a monitor, numeral 3090 an input device, numeral 3100 a bus, and numeral 3110 an image  
15 signal output terminal.

          This motion picture editing apparatus is provided with the CPU 3010 for performing the control of each component of the motion picture editing apparatus and the edition under the control of software (or program), the  
20 monitor 3080 for displaying control information of the CPU 3010 and information concerning edition which includes information of a motion picture, scene images and cut images and information of a hierarchical structure (or tree structure) representing the state of edition, the input  
25 device 3090 such as a mouse or keyboard for selecting information displayed on a screen of the monitor 3080 to make the input of a command to the CPU 3010, the frame buffer memory 3070 for storing image information to be

0022020 272500

displayed on the monitor 3080, the image reproducing device 3040 such as a video tape recorder (VTR) for reading and reproducing from a recording medium an image signal of a motion picture to be used for edition and outputting it to the video interface 3050, the video interface 3050 for receiving the image signal of the motion picture inputted from the image reproducing device 3040 to convert it into image information having a format handled by the motion picture editing apparatus which information is then outputted to the information storage device 3060, the cut change point detecting unit 3030 and the memory 3020 and for receiving image information of the motion picture edited with the format handled by the motion picture editing apparatus and outputted from the information storage device 3060 to convert it into an image signal which is then outputted from the image signal output terminal 3110, the cut change point detecting unit 3030 for comparing adjacent ones of frame images forming a motion picture to separate them from each other under the judgment of the adjacent frame images as belonging to different cut images in the case where a difference between the adjacent frame images has a change exceeding a predetermined quantity, the memory 3020 for storing software for control of the CPU 3010 and temporarily storing various control information (for example, a series of frame numbers for a motion picture, frame numbers of detected cut change points, M-icons or images for the purpose of display to be displayed on the screen of the monitor 3080 and having a



specified object or character from a motion picture source subjected to edition will be described using Figs. 2, 4 and 13.

Fig. 4 shows an editing window on the screen of the monitor 3080 (Fig. 3) of the non-linear editing apparatus.

In order to detect an object or a character (for example, "X"), an operator uses the mouse pointer 810 to select an M-icon corresponding to a cut or scene to be deleted from the editing area 1010 or the material area 1020 by clicking the mouse. At this time, the M-icon is brought into a selected condition. To thus bring an M-icon into a selected condition is called attach (or attaching the M-icon). A method of displaying the selected condition may include, for example, enclosing the selected M-icon by a thick frame, changing the display color of the M-icon, and flickering the M-icon.

For example, M-icons 1031 to 1033 in the material area 1020 shown in Fig. 4 are attached and the character detecting button 1051 in the edition function button group 1050 is then clicked. As a result, a window shown in Fig. 2 is displayed on the monitor 3080. A processing for detecting the character "X" is performed on this window. Fig. 2 is a diagram for explaining a method in which the detection of a specified character is made with the features of that character defined. Reference numeral 300 denotes an identify (ID) window, numeral 301 an OK button, numeral 302 a CANCEL button, numeral 303 a slider knob,

numeral 304 a sliding cursor, numeral 305 an enlarged image, numeral 306 an enlargement display area, numeral 307 an OBJECT button, numeral 308 a color designating frame, numeral 309 a SEARCH button, numeral 311 a still image view slider, numerals 321 to 330 frame images, numeral 809 a film image, numeral 810 a mouse pointer, numeral 815 a BEGIN button, and numeral 816 an END button.

In Fig. 2, frame images 321 to 330 included in the attached M-icons 1031 to 1033 are displayed in the film image 809. The frame images 321 to 330 are arranged in order along a time axis. Right and left portions being not displayed in the window can be viewed by performing a processing for scrolling the slider knob 303 of the still image view slider 311 right and left to slide displayed frame images. This scroll processing is enabled, for example, by moving the mouse pointer 810 to the slider knob 303 and dragging the pointer by the mouse or attaching an arrow portion of the sliding cursor 304. An enlarged frame image 305 is displayed in the enlargement display area 306 at a left/lower portion of the ID window 300. The enlarged frame image 305 is an enlarged version of the leftmost one 321 of the frame images 321 to 330 in the film image 809. In order to perform a processing for detecting the character "X", features to be detected as the character "X" are defined using the enlarged image 305. The frame image 321 displayed at the leftmost and the enlarged image 305 displayed in the enlargement display area 306 are inter-locked with each other. Therefore, the operator can scroll

00544-03000  
00200-04750

a frame image in the film image 809 so that it is displayed in the enlargement display area 306 as the enlarged image 305 which is to be used for the character "X" detection processing. While viewing the enlarged image 305 with the  
5 frame images in the film image 809 scrolled, the operator selects a frame image which is regarded as being optimum in regard to the character "X" detection processing. Next, the combination of specific colors possessed by the character "X" is designated on the basis of the enlarged  
10 image 305. The frame image 321 of the frame images 321 to 330 is shown so that it is displayed with a simple image. The representation of images to be displayed as the other frame images 322 to 330 is omitted from the illustration of Fig. 2.

15           A method of designating the combination of specific colors includes clicking the OBJECT button 307 and then designating a color designating frame 308 in the enlarged image 305 for defining an extent in which a specific color is designated.

20           The designation of the color designating frame 308 is similar to a method of generating a square frame in the case where the drawing is made in a personal computer or the like. It is of course that the movement and size change of the color designating frame 308 after the  
25 designation are possible.

          The color of a portion enclosed by the color designating frame 308 assumes a specific color possessed by the character "X" (or a pixel region occupied by the



character "X" in the frame image). In the example shown in Fig. 2, the color of a dress worn by the character "X" is designated. The others, for example, the color of hair, the color of skin and so forth are designated. Data of the combination of these designated colors is used for the detection processing.

The character detecting function as mentioned above can be provided using a method disclosed by, for example, JP-A-6-223179.

10 After the color designation is completed, the SEARCH button 309 is clicked to perform the detection processing for the M-icons 1031 to 1033. After the detection processing has been performed, the result of detection for the character "X" is displayed on the ID window 300, as shown in Fig. 13. The description of Fig. 13 will be made later on. When the result of detection is to be held, the OK button 301 is clicked, thereby closing the ID window. When the result of detection is not to be held, the CANCEL button 302 is clicked, thereby closing the ID window.

20 Two results are obtained by the character detecting function. One is information of a detection effectuating domain indicative of a coverage or domain throughout which the character "X" exists in an image material or cut. 25 The other is position information indicating where is the character "X" located in frame images of the detection effectuating domain (for example, leftside, central/rightside, upside, left/downside or the like).

00547473-030300

Next, an example of the GUI operation concerning the confirmation or correction of the result of character detection will be described by virtue of the window example shown in Fig. 13. Fig. 13 shows an example of display on the ID window in the case where the confirmation or correction of the result of character detection is made. In Fig. 13, the same parts as those in Fig. 2 are denoted

by the same reference numerals as those used in Fig. 2. Numeral 80 denotes an ID window, numerals 800, 801, 802, 802' and 803 detection arrows, numerals 804, 805, 806, 807 and 808 object frames, numeral 809' a film image, numerals 5 811 and 812 detection effectuating domains, numerals 813, 814, 823 and 824 frame images arranged in the film image 809' in order along the time axis from the left of the window, and numerals 817, 818, 820, 821 and 822 pixel regions which the character "X" occupies in the respective 10 frame images.

On the ID window 80 shown in Fig. 13, detection arrows 800 to 803 displayed on the upper side of a film image 809' are arrows indicating the beginning and end of each detection effectuating domain. The detection arrow 15 800 or the detection arrow 802 is a detected head called a begin point. The detection arrow 801 or the detection arrow 803 is a detected termination called an end point. A domain sandwiched between the detection arrow 800 of the begin point and the detection arrow 801 of the end point is 20 a detection effectuating domain 812, and a domain sandwiched between the detection arrow 802 of the begin point and the detection arrow 803 of the end point is a detection effectuating domain 811. Each of object frames 804 to 808 displayed in frame images belonging to the detection 25 effectuating domain 811 and the detection effectuating domain 812 indicates a position at which the character "X" exists in the frame image. The object frame is displayed as the result of character detection.

002020" E2T250

The change or correction for the detection effectuating domain and the object frame is made as mentioned below. First, the change of the detection effectuating domain will be described.

5 Referring to Fig. 13, the description will be made in conjunction with the case where the detection arrow 802 indicative of the begin point is moved into the frame 813 located on the left side by one frame to elongate the detection effectuating domain 811. The mouse pointer 810 is GUI parts capable of being moved on the window by virtue of a mouse (not shown). The mouse pointer 810 may also be operated by a general pointing device other than the mouse.

First, the mouse pointer 810 is moved to a BEGIN button 815 and the mouse is then clicked. Next, the mouse pointer 810 is moved to the frame 813 and the mouse is then clicked. Thereupon, a detection arrow 802' representing a new begin point is displayed. Thereafter, the detection arrow 802 representing the original begin point is clicked to extinguish the detection arrow 802 of the original begin point. As a result, the detection effectuating domain 811 is enlarged leftwards by one frame. Similarly, a change in end point may be made by clicking an END button 816, clicking a frame for which the setting of a new end point is desired, and thereafter clicking a detection arrow of the original end point.

Next, the change or correction for the object frame will be described. This change too is made using the mouse pointer 810.

The description referring to Fig. 13 will be made in conjunction with an example taken for the case where the object frame 806 of the frame image 814 is changed. In Fig. 13, the object frame 805 of the frame image 824

- 5 approximately coincides in size and position with a pixel region 818 representative of the character "X" whereas the object frame 806 of the frame image 814 has a size somewhat larger than a pixel region 820 of the character "X" and a position nearer to the center than the pixel region 820.
- 10 In this case, when seeing this frame image 814, the operator may be perplexed by the position of the object frame 806 with the result of erroneous recognition that the pixel region of the character "X" resides at a central portion of the frame. Therefore, it is necessary to change
- 15 or correct the size and position of the object frame 806 in order to make conformability to the pixel region 820 of the character "X". The change in size or position of the object frame (804, 805, 806, 807, 808) can be made by use of a method of deleting the present object frame and there-
- 20 instead setting a new frame as well as known methods, for example, screen operation and object operation in Windows 95 which is an operating system (OS) of Microsoft.

- In the case where there is performed the operation of changing the object frame 806 in conformity to the
- 25 pixel region 820 of the character "X", all object frames succeeding the object frame 806 are similarly changed so that they have the same size and position as the changed object frame 806 or they have the same size and position as

002020 227560

the pixel regions of the character "X" (for example, the pixel regions 821 and 822 of the character "X" in the object frames 807 and 808).

When the CANCEL button 302 shown in Fig. 2 is attached in the course of character detection or after the completion thereof, the ID window 300 is closed with the result of detection cancelled. On the other hand, when the OK button 301 on the window 300 is attached, the window 300 is closed with the result of detection held and an IDX icon 12 is displayed at the lower portion of the material area 1020 of the editing window 1000, as shown in Fig. 8. Information concerning the result of detection processing for the character "X" is stored in the data structure of the IDX icon 12.

Such an IDX icon is generated one for all M-icons simultaneously attached in the editing window 1000 for character detection. Namely, if different M-icons are attached respective times for character detection processing, new IDX icons 13, 14, --- are successively generated.

When the IDX icon 12 is double-clicked by the mouse or the IDX icon 12 is selected and an IDX information button 1053 is attached, an IDX window indicative of IDX information as shown in Fig. 6 is pop-up displayed.

Fig. 6 shows an example of display on the IDX window in which the respective results of detection for characters "A", "B" and "C" are displayed. This corresponds to the result when the same group of M-icons 1031 to 1033 is subjected to respective detection processings for

00517173-030200

three different characters. Reference numeral 600 denotes an IDX window, numeral 603 a detection zone display area, numerals 604, 605 and 606 zones, numeral 611 a target display column, numeral 614 a detection effectuating domain, numeral 615 a detection ineffectuating domain, numerals 631, 632 and 633 target images, numerals 634, 635 and 636 character's names, numerals 637, 638 and 639 detection domain bars, numeral 650 a detection result display column, numeral 640 a slider for sliding the display contents of the detection result display column 650 in a lateral direction, numeral 641 a slider for sliding the display contents of the detection result display column 650 in a longitudinal direction, numeral 810 a mouse pointer, and numeral 241 a CLOSE button.

In Fig. 6, a detection zone display area 603 on the IDX window 600 is displayed along a time axis with the lateral direction taken as a progressing direction. Also, the detection zone display area 603 are now divided into three zones 604 to 606. The division to these zones 604 to 606 is made in accordance with the cut length (or the number of frames) of each of the M-icons 1031 to 1033 attached by the operator. Namely, the number of frames of the M-icon 1031 corresponds to the number of frames of the zone 604, the number of frames of the M-icon 1032 corresponds to that of the zone 605, and the number of frames of the M-icon 1033 corresponds to that of the zone 606. Further, in a target display column 611, the target images 631, 632 and 633 of detected characters and the character's

0051773-030200

names 634, 645 and 636 thereof are displayed in the longitudinal direction.

For example, in the case where a character "A" is detected, a target image 631 and a character's name 634 are displayed in a target display column 611 and a detection domain bar 637 is displayed in a detection result display column 650 on the right side of the target display column 611. Further, in the case where a character "B" is detected, a target image 632 and a character's name 635 are displayed on the lower side of the character "A" in the target display column 611 and a detection domain bar 638 is displayed in the detection result display column 650 on the right side of the target display column 611. Similarly, in the case where a character "C" is detected, a target image 633 and a character's name 636 are displayed on the lower side of the character "B" in the target display column 611 and a detection domain bar 639 is displayed in the detection result display column 650 on the right side of the target display column 611. The target image 631, 632 or 633 is a frame image (for example, the frame image 305 in Fig. 2) in an enlarged display form used for acquiring specific colors to detect the character "A", "B" or "C". The character's names 634 to 636 under the target images 631 to 633 have the respective names of objects of detection displayed therein. Since the display column for the detection domain bars 637, 638 and 639 is limited, there may be the case where a detection area is so large that the whole of the detection area cannot be displayed at once.

0051713-030200



5 (In the example shown in Fig. 6, the number of characters capable of being displayed at once is 3.) In this case, a slider 641 is operated to scroll the display in the longitudinal direction.

Next, the result of detection will be described with the detection domain bar 637 taken as one example.

15           A detection effectuating domain 614 indicates a domain where the character "A" is detected (or the detection of the character "A" is effectuated) in the zones 604, 605 and 606 with regard to the M-icons 1031 to 1033. A detection ineffectuating domain 616 indicates a domain  
20 where the character "A" is not detected (or the detection of the character "A" is ineffectuated). For example, the zone 604 includes a time-sequential array of frame images collected in association with the M-icon 1031, the zone 605 includes a time-sequential array of frame images collected  
25 in association with the M-icon 1032, and the zone 606 includes a time-sequential array of frame images collected in association with the M-icon 1033. The zone is represented with a predetermined width applied for each

frame image. In Fig. 6, the detection effectuating domain 614 and the detection ineffectuating domain 616 are represented in a distinctive manner so that the former has an oblique line pattern and the latter has a white pattern.

- 5 The representation of effectuation/ineffectuation of detection may be arbitrary so long as the distinction from each other is provided. For example, the detection effectuating and ineffectuating domains 614 and 616 may be displayed with orange and grey colors, respectively, or one  
10 of the domains 614 and 616 may be flickered.

The detection effectuating domain 614 and the detection ineffectuating domain 616 are also displayed on the side faces of the M-icons 1031 to 1033 shown in Fig. 8.

- Figs. 12A, 12B and 12C are views showing that the  
15 results of character detection are displayed on the side faces of the M-icons 1031 to 1033 shown in Fig. 8. As in Fig. 6, zones 604, 605 and 606 are ones for the M-icons 1031, 1032 and 1033, respectively. The width of the side face of the M-icon indicates the number of frames of that  
20 M-icon itself (or is represented with a fixed thickness for each one frame image). For the detection effectuating domain 614, the side face of the M-icon 1031, 1032 or 1033 is displayed with oblique lines by the corresponding number of frames. For the detection ineffectuating domain 616,  
25 the side face of the M-icon is displayed with a white color by the corresponding number of frames. The display of such domains may be set such that it is always made as the result of detection or is usually made in the case where

002020 "E277550



5 for confirmation.

unnecessary detection result from the window.

processing for another M-Icon.

possible and a high functionality is available.

Thereby, it is not necessary to generate IDX icons.

5

15

20

There are further provided a preview function with which only a detection effectuating domain obtained by

5 the data structure.

10 like freely.

the corresponding M-icon so that it can be reused.

15           An embodiment of the present invention will now be described. The successive description of the procedure of operation referring to Figs. 4 to 10 will be made starting from a state in which a processing for detection of a specified character has never been performed.

20           Start from the screen of Fig. 4 which shows an example of an editing window displayed on the screen of the monitor 3080 in the motion picture editing apparatus shown in Fig. 3.

In order to detect a character "A", an operator  
25 first attaches M-icons 1031 to 1033 corresponding to cuts  
or scenes made an object of detection. Then, the operator  
attaches the character detecting button 1051 in the edition  
function button group 1050. As a result, an IDX window

Fig. 5 shows an example of the IDX window in a state in an initial state or a state in which a character detection processing has not yet been performed. Reference numeral 6000 denotes an IDX window, numerals 237, 238 and 239 detection result display columns, numeral 240 a NEW button, numeral 241 a CLOSE button, numeral 242 a SEARCH button, numeral 243 a COMBINE button, numeral 244 an UNCOMBINE button, numeral 245 a PREVIEW button, numeral 246 an INFORMATION button, numeral 247 a visual range adjusting slider, and numeral an ADJUST button. Other numerals are the same those used in Fig. 6.

This stage is a state in which the detection processing has never been performed for the M-icons 1031 to 1033. Therefore, neither the target display column 611 nor the detection result display columns 237, 238 and 239 on the IDX window 6000 has data displayed therein, as shown in Fig. 5. This state is an initial state.

First, the detection processing is initiated for  
20 the character "A".

When the operator clicks the NEW button 240, an ID window 300 shown in Fig. 2 is displayed on the monitor 3080. On this ID window 300, the operator performs the detection processing for the character "A". The details of the operation for this detection processing have already been described.

After the detection processing is performed, the result of detection for the character "A" is displayed on

5           At a point of time when the OK button 301 is  
clicked, data of the result of detection for the character  
"A" is stored into data structures corresponding to the  
attached M-icons 1031 to 1033. However, in the case where  
an upper layer of the tree structure, for example, an  
10 M-icon 1220 "a" (Fig. 8) is attached, the data of the  
result of detection is stored into data structures corre-  
sponding to M-icons 1210 "b", "c" and "d" in the lowermost  
layer of the tree structure. The reason why the detection  
result data is always stored in the lowermost M-icons is  
15 that the detection result data is prevented from being  
affected by an editing operation in the editing area 1010.  
Namely, if data of the result of detection for the lower-  
most layer M-icons 1210 "b", "c" and "d" is stored in the  
M-icon 1220 "a" of the upper layer of the tree structure, a  
20 change in detection result data may be required, for  
example, in the case where the M-icon 1210 "c" is removed  
from the tree structure. The procedure for thus storing  
data of the result of detection always in the information  
region of an M-icon of the lowermost layer of the hierar-  
25 chical structure will be described later on in reference to  
a flow chart shown in Fig. 33.

When the ID window 300 is closed, there returns to the display of the IDX window again. In this case, the



result of detection concerning the character "A" is displayed on the IDX window, as shown in Fig. 7. Fig. 7 shows the IDX window on which only the result of detection concerning the character "A" is displayed. Reference numeral 6001 denotes an IDX window, numeral 631 a target image of the character "A", numeral 634 a character's name, and numeral 637 a detection domain bar. The other numerals are the same as those used in Fig. 5.

When the CLOSE button 241 is clicked, there  
10 returns to the editing window 1000 shown in Fig. 4.

Further, the detection processing is also performed for characters "B" and "C". However, an M-icon made an object of detection is changed. By way of example, it is assumed that the M-icons 1031 and 1033 are attached when the detection processing is to be performed for the character "B" and only the M-icon 1032 is attached when the detection processing is to be performed for the character "C". The description of an operation of this detection processing will be omitted since the operation is similar to that mentioned above.

After the detection processing for the characters "B" and "C" is completed, the M-icons 1031 to 1033 are attached again to open the IDX window 600. An example of this state is shown in Fig. 1. Fig. 1 shows an embodiment of the IDX window. In Fig. 1, parts having the same functions as those in Fig. 7 are denoted by the same reference numerals as those used in Fig. 7. Numeral 600 denotes an IDX window, and numerals 250, 251 and 252 denote

The portions of the detection unsubjected zones 250 to 252 represent frame information of M-icons in regard to which no detection processing has been performed.

This representation of the state of "having not  
25 yet been subjected to detection processing" is also  
reflected on the side face of an attached M-icon. For  
example, consider the result of detection for the character  
"B". An operation is performed by attaching the target

image 632. When the target image 632 is attached, the M-icon 1032 is displayed so that the whole of the side face thereof has a color representing the detection unsubjected zone 250 having not yet been subjected to detection

5 processing, as shown in Fig. 9B, since the M-icon 1032 has not yet been subjected to detection processing for the character "B" and the width of the side face of the M-icon indicates the number of frames of the M-icon itself. Figs. 9A, 9B and 9C are views showing that the result of detection for the character "B" is displayed on the side faces of the M-icons 1031 to 1033 shown in Fig. 4. As in the case of Fig. 6, zones 604, 605 and 606 are ones for the M-icons 1031, 1032 and 1033, respectively.

10  
15 Thereby, the representation of an M-icon having not yet been subjected to detection processing is also enabled on the editing window 1000.

Further, since data of the combination of colors used in the detection processings for the character "A", "B" or "C" is preserved in the data structure of an M-icon, it becomes possible to use this data for an M-icon portion having not yet been subjected to detection processing. By way of example, there will now be described the case where a detection processing is to be performed for the character "C" in regard to zones having not yet been subjected to  
20 detection processing, that is, the M-icons 1031 and 1033, as indicated by the detection unsubjected zones 251 and 252. First, the target image 633 is attached and a SEARCH button 242 is then clicked. As a result, the M-icons 1031

002020-037750

and 1033 are subjected to a detection processing by use of data of the combination of colors used in the processing for detection of the character "C".

An example of the result of detection mentioned in the above is shown in Fig. 10. Fig. 10 is a diagram showing an embodiment of an IDX window according to the present invention. In Fig. 10, the same parts as those in Fig. 1 are denoted by the same reference numerals as those used in Fig. 1. Numeral 6003 denotes an IDX window, numeral 280 a new detection effectuating domain representing a portion where the character "C" is detected, and numeral 282 a new detection ineffectuating domain representing a portion where the character "C" is not detected. Thus, the detection effectuating and ineffectuating domains 280 and 282 are newly added. The procedure for distinctively displaying a zone having already been subjected to detection processing and a zone having not yet been subjected to detection processing will be described later on in reference to Figs. 34 and 35.

20           This function provides the following merits. A  
first merit is that when a detection processing for the  
character "C" is to be performed for the M-icons 1031 and  
1033, it is not necessary to designate the combination of  
colors again. Also, since the preserved data of color  
25 combination is used as it is, the detection processing can  
be performed with the same condition as that for the M-icon  
1032. Further, since data of the result of detection is  
stored for each M-icon, it becomes possible to find out

only the M-icons 1031 and 1033 having no result of detection concerning the character "C", thereby subjecting only such M-icons to detection processing. Thereby, it is possible to reduce a time required for the detection processing.

Next, the description will be made of the improvement in function of the IDX window.

First, there is provided a combining function of combining the results of detection. This combining function is used, for example, in the case where provided that the characters "A" and "B" are fellow friends, it is desired to handle the results of detection for the two characters in a form combined into one within the framework of fellow friends. There are two ways of combinative handling, that is, a method in which a new detection effectuating domain is provided with frames where either the character "A" or the character "B" exists (OR condition) and a method in which a new detection effectuating domain is provided with frames where both the character "A" and the character "B" exist together (AND condition). An operation for this purpose is performed by clicking a COMBINE button 243 after the attachment of the target image 631 of the character "A" and the target image 632 of the character "B". Fig. 11 is a diagram showing one embodiment of the combination. In Fig. 11, the same parts as those in Fig. 10 are denoted by the same reference numerals as those used in Fig. 10. Numeral 6002 denotes an IDX window, numeral 380 a detection effectuating domain, numeral 383 a

0051713 030200

detection ineffectuating domain, numeral 387 a combine  
mark, numeral 661 a detection domain bar representing the  
result of detection of frames where either the character  
"A" or the character "B" exists, and numeral 663 a target  
5 image.

In Fig. 11, a detection domain bar 661 is  
displayed with detection effectuating domains 380 in the  
case where frames containing either the character "A" or  
the character "B" are taken as a new detection effectuating  
10 domain. Also, a target image 663 is displayed with one 631  
of the attached target images concerning the character "A"  
located at an upper position on the IDX window (Fig. 10).  
A combine mark 387 (for example, "C") representative of the  
combination is added to a left/upper portion of the target  
15 image. The result of detection of the character "C" is  
displayed in a manner sited close upwards by one stage.

There is also provided an uncombining function  
contrary to the combining function. The uncombining  
function is a function of restoring the combinative detec-  
20 tion result to the original results of detection. In  
operation for this purpose, the combined target image 633  
is attached and a UNCOMBINE button 244 is thereafter  
clicked by the mouse. As a result, there returns to the  
state shown in Fig. 1.

25 With the combining and uncombining functions, the  
results of detection individually provided for respective  
characters can be arranged or integrated in terms of  
abstract contents of, for example, "fellow friends".

00517173-030200

Next, a detection result deleting function will be described. This function is a function of deleting an unnecessary result of detection from the structure data of an M-icon. In an operation for this purpose, for example, 5 in the case where the result of detection of the character "A" is to be deleted, the target image 631 (Fig. 1) is attached and a DELETE key of the keyboard 3090 is thereafter depressed. Thereby, the result of detection concerning the character "A" is deleted from the data structure of 10 the M-icon as well as the IDX window. And, the remaining results of detection concerning the characters "B" and "C" are displayed on the IDX window in a manner sited close upwards.

Next, a preview function will be described. This 15 preview function is a function of movie-reproducing only a detection effectuating zone obtained by a detection processing. In an operation for this purpose, for example, in the case where detection effectuating zones for the character "A" are to be previewed, the target image 631 of 20 the character "A" is attached and a PREVIEW button 245 is thereafter clicked. As a result, a motion picture reproducing window is displayed in the editing window 1000 and only the frames of detection effectuating domains 214 to 215 are previewed by the reproduction. Thereby, it is 25 possible to confirm the detection effectuating domain by means of a motion picture.

Next, an information function will be described. This information function is a function with which informa-

005173-030200

tion such as information of a character subjected to detection processing is added to the result of detection and this information added detection result is stored into the data structure of an M-icon. In an operation for this purpose, for example, in the case where it is desired to see or record information concerning the character "A", the target image 631 of the character "A" is attached and an INFORMATION button 246 is thereafter clicked. Thereby, it is possible to add information (for example, name, birth date and so forth) for the character "A" to the result of detection of the character "A".

A detection result adjusting function is performed, for example, in the case where the result of detection of the character "A" is to be adjusted. This is performed by attaching the target image 631 of the character "A" and thereafter clicking an ADJUST button 248.

Finally, there will be described a function of adjusting a visible range of the result of detection displayed in the detection domain bar shown in Fig. 1. This adjustment of the visible range of the result of detection is made by dragging a visible range adjusting slider 247. In the case where a numeral displayed on the visible range adjusting slider 247 is "1", the visible range on the detection domain bar is one second, that is, 30 frames. By moving the visible range adjusting slider 247, it is possible to freely changing the display width of a detection effectuating domain or the number of frames of an M-icon. With the use of this function, however large

005173-030200



the number of frames possessed by an M-icon to be displayed is, the M-icon can be displayed with a display width reduced to allow to take a look at it. Also, even a detection effectuating domain having only one frame can be  
5 displayed with a display width enlarged. The unit of a numeral displayed on the visible range adjusting slider 247 can be set arbitrarily. For example, it may be the number of frames.

In the foregoing embodiment, one example of the  
10 image detecting method has been described in conjunction with an example in which a character is detected. However, it is self-evident that an object image other than characters can be detected by designating the combination of specific colors. Further, it is needless to say that  
15 the present invention can also be applied in conjunction with a detecting method other than that mentioned above.

According to the embodiment of the present invention mentioned above, the result of a detection processing is stored in the data structure of an M-icon.  
20 Thereby, the representation of an M-icon having already been subjected to detection processing and the representation of an M-icon having not yet been subjected to detection processing are enabled on an IDX window and on the side face of the M-icon.

25 A second effect of the embodiment of the present invention is that with the construction in which data of the combination of colors used in a detection processing is preserved in the data structure of an M-icon, it becomes

00517473-030200

A third effect of the embodiment of the present invention is that the improvement in functionality of an IDX window is attained by newly adding a combining/uncombining function, a deleting function, a preview function, an information function and a visible range adjusting function for the result of detection.

In Fig. 14, frame images 521 to 330 as a part of

frame images included in attached M-icons 1030, 1034 and 103A (Fig. 4) are displayed in the film image 501. The frame images 521 to 530 are arranged in order along a time axis. Right and left portions being not displayed in the window can be viewed by performing a processing for scrolling the slider knob 509 of the still image view slider 508 right and left to slide frame images. This right/left scroll processing is enabled, for example, by moving the mouse pointer 810 to the slider knob 509 and dragging the mouse pointer by the mouse or attaching an arrow portion of the slider cursor 532. The display frame unit changing slider 510 is a slider for setting every what frames are the frame images 521 to 530 in the film image to be displayed. In an example shown in Fig. 14, since a value set by the display frame unit changing slider 510 is "1", the frame images are displayed every frame. The set value can be changed up to, for example, "90". If the value is set to "90", the frame images will be displayed every 90 frames so that 10 frame images displayed in the film image 501 represent a part of 900 frame images.

An enlarged frame image 520 is displayed in the enlargement display area 502 at a left/lower portion of the ID panel 500. This enlarged frame image 520 is an enlarged version of the leftmost one 521 of the frame images 521 to 530 in the film image 501. In order to perform a processing for detecting a character "X", features to be detected as the character "X" are defined using the enlarged image 520. The frame image 521 displayed at the leftmost and the

0051713"030000

A method of designating the combination of specific colors includes attaching the OBJECT button 545 and then designating that color designating frames 503 to 505 in the enlarged image 520 each of which defines an extent for designating a specific color. The number of the color designating frames may be any value equal to or larger than one. The size and the form of the color designating frame can be designated. The others of the window shown in Fig. 14 are similar to the window shown in Fig. 2.

09547473-030200

necessary to operating three windows (or the ID panel, the  
IDX panel and the editing window) for character detection.  
However, there is a problem that since these windows are  
individually displayed on the monitor in the case where a  
5 function established (or built in) for each window is set  
or performed, it is not possible to make occasional  
confirmation of a relationship between the panels and a  
relationship between the material area and the editing area  
in the editing window on which the edition of a motion  
10 picture itself is performed.

The embodiment described in below solves the  
above problem, thereby providing an editing method in which  
the result of generation and correction of data on an ID  
panel and an editing widow can be recognized on an IDX  
15 panel at a look.

In the motion picture editing method of the  
present embodiment, two panels and an editing window as  
mentioned above are always displayed. Further, a process-  
ing on one of the two panels is simultaneously reflected on  
20 the other panel and also displayed on M-icons on the  
editing window, thereby enabling the realization of a  
motion picture editing method which is used in a motion  
picture editing apparatus for selecting icons as image  
materials displayed on a display screen to make edition  
25 based on a screen display operation and in which when  
M-icons as image materials to be edited are selected, the  
sequence of combination in the edition is displayed  
together with the M-icons, thereby facilitating an editing

work.

Now, the mutual operation of an ID panel, an IDX panel, an editing area 1010 and a material area 1020 in a character detecting function according to the present invention will be described in accordance with the actual procedure of a detection processing.

When an operator selects M-icons 1030, 1034 and 103A on the editing window 1000 of Fig. 4 having already been described, this selection can be recognized in a form in which the selected M-icons 1030, 1034 and 103A are enclosed by thick color frames (for example, red solid lines), as shown in Fig. 15.

Fig. 15 is a diagram showing an embodiment of the editing window when M-icons are selected. In Fig. 15, the same parts as those in Fig. 4 are denoted by the same reference numerals as those used in Fig. 4. Numeral 1000 denotes an editing window. Thus, the operator first selects M-icons in a section which is to be subjected to a processing for detection of a character. In this case, the number of selected M-icons may be plural. The selected M-icons may be ones in either the editing area 1010 or the material area 1020 or over both these areas. They may be upper M-icons in a tree structure.

Next, a character detecting button 1051 in an edition function button switch group 1050 is clicked. Then, an ID panel is displayed on the monitor 3080 so that it overlaps a part or the whole of the editing window 1000. Fig. 16 is a diagram showing an example in which an ID

panel 500' is displayed to cover the editing window 1000 fully. Fig. 16 shows an initial state of the ID panel. In Fig. 16, the same parts as those in the ID panel shown in Fig. 14 are denoted by the same reference numerals as those in Fig. 14. Numeral 500' denotes an ID panel.

In Fig. 16, the frame images of ten leading frames are displayed as a film image 501 on the ID panel 500' which is the display window of the ID panel in the initial state. Also, a frame image designated by the operator is displayed in an enlargement display area 502. In Fig. 16, the illustration of each frame image as the film image 501 is omitted.

In a first step for detection, the operator selects a desired frame image (in which a character to be detected exists) from the film image 501 displayed on the ID panel 500' so that it is dragged and dropped to the enlargement display area 502.

At this time, a frame image corresponding to the selected frame and read from the information storage device 3060 (or a version thereof trimmed into a proper size) is displayed as an enlarged image 520 in the enlargement display area 502, as shown in Fig. 14. Next, the operator selects color designating frames 503, 504 and 505 indicative of the extents for designation of specific colors with respect to the character "X" as an object of detection from the enlarged image 520 and turns on an AUTOMATIC SEARCH button 511, thereby initiating a detection processing. Since the operation of the detection processing has already

Fig. 17 is a diagram showing an embodiment of the ID panel of the present invention. It is shown that object frames are additionally displayed on the ID panel shown in

Fig. 14. In Fig. 17, the same parts as those in Fig. 14 are denoted by the same reference numerals as those used in Fig. 14. Numeral 500" denotes an ID panel, numeral 531 a detection effectuating domain, numeral 506 a detection arrow representing a begin point of the detection effectuating domain 531, numeral 507 a detection arrow representing an end point of the detection effectuating domain 531, and numerals 561 to 563 object frames.

Namely, when a detection processing is performed on the ID panel 500 shown in Fig. 14, the detection processing is performed for each frame to be subjected to detection so that regions having a character "X" therein and their frame numbers are stored. When the detection processing is completed, frames resulting in the effectuation of detection of the character "X" are sandwiched between a detection arrow 506 (or a begin point) and a detection arrow 507 (an end point) on a film image 501 of the ID panel 500", as shown in Fig. 17. Further, pixel regions having the character "X" therein are displayed in a form enclosed by object frames 561 to 563. In Fig. 17, frame images resulting in the ineffectuation of detection of the character "X" are omitted from the illustration.

In Fig. 17, if the result of detection of the



character "X" is satisfactory, the operator turns on an OK button 541 so that the ID panel 500" is displayed with a reduced size at a predetermined location on the monitor 3080, for example, a left/upper portion thereof. At the same time, an IDX panel 600 as shown in Fig. 6 is displayed covering the editing window 1000 and the ID panel. On this IDX panel 600, there is displayed the result of the character detection processing performed in the above. After the confirmation of the result of detection is completed in this state, a CLOSE button 241 is turned on so that the ID panel is displayed with a reduced size at a predetermined location on the monitor 3080, for example, a right/upper corner portion thereof.

Though each of the ID panel and the IDX panel is displayed on the monitor 3080 in a reduced state, its display size can arbitrarily changed (enlarged or reduced). For example, in order that for the convenience of an operation only a part of the panel can be seen, it may be displayed in an enlarged form. After the completion of the operation, the panel may be displayed on a predetermined location of the monitor 3080 with an reduced size mentioned above.

An example of the multiple window display in this state is shown in Fig. 18. Fig. 18 is a diagram showing an embodiment of the present embodiment in which an ID panel, an IDX panel and an editing window (that is, an editing area and a material area) are simultaneously displayed on the monitor 3080. Reference numeral 1000 denotes the

editing window, numeral 1010 the editing area, numeral 1020 the material area, numeral 500 the ID panel, and numeral 600 the IDX panel.

Since the display contents of the editing window, 5 the ID panel and the IDX panel shown in Fig. 18 are changed, on an editing operation performed by the operator, in accordance with the contents of the editing operation, the description of the details thereof will be omitted.

First, the description concerning Fig. 18 will be 10 made in reference to the editing window 1000 shown in Fig. 4, the ID panel 500' shown in Fig. 16 and the IDX panel 6000 shown in Fig. 5.

In Fig. 18, the editing window 1000 shown in Fig. 4 is displayed on the monitor 3080. Further, the ID panel 15 500' shown in Fig. 16 and the IDX panel 6000 shown in Fig. 5 are displayed as an ID panel 500 and an IDX panel 600 so that they overlap the editing window 1000 at an upper portion thereof.

When the operator selects M-icons 1030, 1034 and 20 103A on the editing window 1000 shown in Fig. 4, the selected M-icons 1030, 1034 and 103A are enclosed by thick color frames (for example, flickered red solid lines), as shown in Fig. 15. Thus, the selection of those M-icons can be recognized at a look. Simultaneously, the display of 25 the ID panel changes to the ID panel 500 shown in Fig. 14. Also, the frame images of ten leading frames are displayed as a film image 501.

Next, in the case where all the M-icons 1030,

002020-2272500

1034 and 103A selected by the operator have never been subjected to detection processing, the IDX panel 6000 shown in Fig. 18 is such that target image display areas 291, 292 and 293 and detection result display areas 237, 238 and 239 are all blank, as shown by the IDX panel 6000 of Fig. 5.

In the case where the detection is to be performed, a desired frame image 521 containing a character or object to be detected is selected from the film image 501 displayed on the ID panel 500, as has already been described in conjunction with Figs. 14 and 16, so that it is dragged and dropped to the enlargement display area 502. And, a frame image read from the information storage device 3060 (or a version thereof trimmed into a proper size) is displayed as an enlarged image 520 in the enlargement display area 502. Next, the operator selects color designating frames 503, 504 and 505 indicative of the extents of designation of specific colors for an image as an object of detection (for example, the character "X" in this case) from the enlarged image 520 and turns on an AUTOMATIC SEARCH button 511, thereby initiating a detection processing. In the case where the display window of the ID panel 500 is so small that it is hard to see, the ID panel 500 is displayed with a properly enlarged size.

Here, the frame image 521 dragged and dropped to the enlargement display area 502 is the target image 631. This frame image is displayed as the synoptical display area 611 for the target image 631 on the IDX panel 600 having already been described in conjunction with Fig. 6.

00202000-00000000

At the same time, the detected conditions or the result of detection mentioned above are reflected by the IDX panel 600 and the editing window 1000 (Fig. 18) in accordance with the present invention.

Further, the IDX panel 600 of Fig. 18 assumes an IDX panel as shown in Fig. 19. The IDX panel shown in Fig. 19 shows an embodiment of the display on the IDX panel 600 shown in Fig. 18. In Fig. 19, the same parts as those in Figs. 5 and 6 are denoted by the reference numerals as those used in Figs. 5 and 6. Numeral 614' denotes the representation of a newly added detection effectuating domain area, and numeral 616' denotes the representation of

00517173-030200

a deleted detection effectuating domain area. The area representations 614' and 616' will be described later on. In Fig. 19, a target image 631 is displayed in a target image display area 611 while the conditions of frames 5 subjected to detection processing are displayed in a detection domain bar 637 in units of one frame. Namely, in the detection domain bar 637 including divisional zones 604, 605 and 606 in units of the selected M-icons 1030, 1034 and 103A, a domain 614 resulting in the effectuation of 10 detection of the character "X" is showily (or heavily) colored or patterned in units of one frame, thereby representing frame positions at which the character "X" exists.

With the construction, as shown in Fig. 18, in 15 which the ID panel 500 and the IDX panel 600 are displayed together with the editing window 1000 to reflect the detected conditions or the result of detection into other information display columns, it is possible to make confirmation in M-icon units (on the IDX panel) and in 20 frame units (on the ID panel and the IDX panel).

Next, the description will be made of a displaying method in the case where the result of detection is to be corrected. Though a correcting work may include the correction of the detection effectuating domain 531 shown 25 in Fig. 17 (that is, the domain sandwiched between the detection arrows 506 and 507) and the correction of the object frames 561, 562 and 563, the correction of the detection effectuating domain will be made in the case of

linkage display. This work is performed in such a manner that on the ID panel 500" of Fig. 17 displayed as the ID panel 500 in Fig. 18, frames to be subjected to correction are displayed in the film image 501 and the detection arrow 506 indicative of a begin point or the detection arrow 507 indicative of an end point is then dragged by the mouse pointer 810. When this correction work is performed, the IDX 600 displayed in Fig. 18 together with the ID panel 500 assumes the IDX panel 600 of Fig. 19 in which the detection effectuating domain 614 for the character "X" is being displayed in the detection domain bar 637. Therefore, if any frame position in the zones of M-icons subjected to the detection processing in the detection domain bar is double-clicked by the mouse, it is possible to display image data of the corresponding frame so that it is located at the head of the film image 501 (or the left extreme of the ID panel). As a result, a work of displaying a desired frame on the film image in order to correct or confirm the result of detection is facilitated. This also holds for the case where a detection effectuating domain is newly added. At this time, a beam representation 10 as shown in Fig. 20 is applied for the corresponding M-icon on the editing window 1000.

Next, the operation on the ID panel 500 side will be described in more detail.

First, there will be described the case where the detection effectuating domain 531 shown in Fig. 17 is corrected. This is realized by moving the mouse pointer

5

10

15

20

25

The above similarly holds for the case where the result of detection is to be deleted or cleared. In this case, a detection effectuating domain CLEAR button 514 is turned on in lieu of the detection effectuating domain ADD button 512. At this time, the area representation 616' of a deleted detection effectuating domain in the detection domain bar 637 is provided with a different color, a different pattern, the combination thereof or the like in order that it is distinguishable from the representation in the case where detection effectuating frames are showily colored or patterned and the representation in the case where a detection effectuating domain is added.

Next, a further embodiment will be described in  
15 conjunction with the case where the detection processing  
was previously performed one or more times.

Herein, the description will be made in connection to the case where a tree structure 1040 (Fig. 21) having already been subjected to editing work is invoked from the information storage device 3060. Fig. 21 is a diagram showing an editing window in an embodiment of the present invention. In Fig. 21, the same parts as those in Fig. 8 are denoted by the same reference numerals as those used in Fig. 8. Numeral 1000' denotes an editing window, numeral 11 an IDX icon, and numerals 121A, 121B, 121C, ---, 121H, 121I, --- M-icons representing the lowermost cut images in an editing area 1010. Also, it is assumed that this tree structure 1040 was previously subjected to



detection processing once with the uppermost M-icon 1240 selected (that is, with all the M-icons of the lowermost layer taken as a section to be subjected to detection processing).

5 First, the description will be made of the case where a character detecting button 1051 is turned on with the uppermost M-icon 1240 selected for the tree structure 1040. As shown in Fig. 20, an ID panel 500 and an IDX panel 600 are displayed on an editing window 1000 of the monitor 3080. At this time, ten leading frames of the M-icon 121A at the head (or left extreme) of the lowermost layer shown in Fig. 21 are displayed as a film image 501 on the ID panel 500. On the IDX panel 600, a target image 631 designated at the time of detection is displayed in a target image synopsis display area 611 and the conditions of frames subjected to detection processing are displayed in a detection result bar 637, as shown in Fig. 19.

In this state, however, the result of the previous detection processing is not displayed on the ID panel 500. In order to display this detection result, a  
20 desired target image 631 (Fig. 19) on the IDX panel 600 is clicked. Thereby, image data of the frame of the target image 631 and color designating frames 503, 504 and 505 used for color designation are simultaneously displayed in  
25 an enlargement display area 502 (Fig. 14) on the ID panel 500. Further, a detection arrow 506 indicative of a begin point and a detection arrow 507 indicative of an end point are displayed in the film image 501. Frame images 521, 522

Next, consider the case where an M-icon is newly added from the material area in a state in which the tree structure 1040 is invoked. Figs. 22 and 20 are diagrams showing an editing window in an embodiment of the present invention. In Fig. 22, the same parts as those in Fig. 21 are denoted by the same reference numerals as those used in Fig. 21. Numeral 1001 denotes an editing window, numeral 1040' a tree structure in the editing area 1020, numeral 121Z an M-icon newly inserted between the M-icon 121A and 121B, numeral 11' an IDX icon, and numeral 1053 an IDX information button. Fig. 20 shows an embodiment in which a beam representation 10 is additionally displayed on the display window shown in Fig. 18. Fig. 23 shows an example

of the case where a new zone is added after the M-icon 103A for the zone 604. Fig. 23 shows an IDX panel in an embodiment of the present invention as an example of display of the IDX panel shown in Fig. 18. In Fig. 23, the same parts as those in Fig. 19 are denoted by the same reference numerals as those used in Fig. 19. Numeral 6001 denotes an IDX panel, numeral 607 a newly added zone, and numeral 608 a detection unprocessed zone (or a zone having not yet been subjected to detection processing) in the detection domain bar 637 indicating the location of newly added frame images. Fig. 24 is a diagram showing an ID panel in an embodiment of the present invention. In Fig. 24, the same parts as those in Fig. 16 are denoted by the same reference numerals as those used in Fig. 16. Numeral 5000 denotes an ID panel, numeral 901 a detection unprocessed zone, numeral 902 a film image, numeral 903 a detection arrow, and numeral 904 a frame portion.

In Fig. 22, since the detection unprocessed M-icon 121Z is inserted between the M-icons 121A and 121B in the course of edition of a motion picture, the tree structure 1040' has the coexistence of M-icons having already been subjected to detection processing for a certain character "X" (that is, the zones 604, 605 and 606 having already been subjected to the detection of the character "X") and an M-icon having not yet been subjected to detection processing (that is, the zone 607 having not yet been subjected to the detection of the character "X"). When the character detecting button 1051 is turned on in

this state, the zone for the M-icon 121Z having not yet been subjected to detection processing is displayed on the ID panel and the IDX panel to clarify the existence thereof so that it is showily colored or patterned with a color different from colors indicative of frames subjected to detection processing or colors indicative of selected zones.

For example, on the ID panel, the frame portion 904 of the detection unprocessed zone 901 in the film image 902 is showily colored or patterned with a discriminative color or pattern or the combination thereof, as shown in Fig. 24. On the IDX panel, the detection unprocessed zone 608 is showily colored or patterned with the different color or pattern or the combination thereof, as shown in Fig. 23 and mentioned above. In the shown example, the detection of the character "X" is effectuated in all regions of the detection zone 607. In the case where the operator desires to make the character detection for images in the detection unprocessed zone 901, the operator double-clicks the detection unprocessed zone representation 608 on the IDX panel 6001. At this time, ten leading frame images in the detection unprocessed zone 608 are displayed in the film image 901 on the ID panel 5001. At the same time, a beam representation 10 is provided for the M-icon 103Z corresponding to the detection unprocessed zone 608. Thereby, the specification of an M-icon under edition and a relationship between that M-icon and an editing work become clear. The beam representation 10 is a beam-bike represen-

tation which makes the interconnection of those data representations on separate windows which have a relation therebetween, as shown in Fig. 20. The form, color, pattern, etc. of the beam representation 10 may be arbitrary. For example, the beam representation 10 can be displayed in a discriminative mode which changes depending on the amount of information or the contents of information.

Though a sequence in accordance with which zones to be newly subjected to detection processing are added on the IDX panel follows the sequence of edited tree structures in the editing area, the sequence of addition may be the sequence of attachment or the sequence of display in the material area.

Now, the description will be made of the case where a detection processing is actually performed. At this time, number information of M-icons having already been subjected to detection is stored in the memory 3020. Therefore, it is only required to make the detection for frames of an M-icon having not yet been subjected to detection processing. On the ID panel, the result of detection is distinctively displayed with a detection arrow 506 (indicative of a begin point) and a detection arrow 507 (indicative of an end point) the colors of which are different from those of detection arrows for the already performed detection processing. On the IDX panel, frames subjected to the present detection processing are clarified so that they are showily patterned with a color different

002020-173-030200

from that of frames having already been subjected to detection. This representation with different color is finished when the operator moves the detection arrow 506 or 507 or turns on the OK button 541. When the tree structure is  
5 invoked again, such representation with different color turns to the representation having the same color as the detection arrows for the already performed detection processing.

Finally, these panels are closed by turning on  
10 the OK button 541 or the CANCEL button 542 on the ID panel 500 to complete the editing work.

The editing window, the ID panel and the IDX panel can be moved by use of the input device 3090 such as a mouse.

15 Figs. 25 and 26 are diagrams showing an embodiment of the editing window according to the present invention. Fig. 25 is substantially the same as Fig. 18. In Figs. 25 and 26, reference numerals 201, 202 and 203 denote monitor display screens, numerals 50' and 50" ID  
20 panels, numerals 60' and 60" IDX panels, and numerals 100' and 100" editing windows.

As shown in Fig. 25, the displayed editing window 100', ID panel 50' and IDX panel 60' may be positioned so that one or all of the panels do not overlap. The monitor  
25 3080 may be constructed so that it has the plurality of display screens 201, 202 and 203 on which the ID panel 50", the editing window 100" and the IDX panel 60" are displayed, respectively, as shown in Fig. 26. Also, a

00517173-030200

plurality of monitors may be provided. In this case, a beam representation becomes possible, for example, by preliminarily informing the CPU 3010 of the installation positions of the monitors 201, 202 and 203.

5           According to the foregoing embodiments, when the edition of a motion picture is made using a motion picture editing apparatus, the contents of change made in an editing work are displayed on an ID panel and an IDX panel simultaneously. Therefore, it becomes possible to perform  
10 a work of confirming information of the respective panels (with the actual image data seen on the ID panel in units of one frame and seen on the IDX panel in units of one M-icon or frames corresponding thereto). As a result, it is possible to improve the efficiency of edition.

15           In the foregoing embodiments, there is the following problem. In order that after the detection of a specified image such as a character or the like, a domain resulting in the effectuation of detection of the specified image is to be changed, it is required that an operation of  
20 newly generating a begin point and an operation of deleting the original begin point should be performed or an operation of newly generating an end point and an operation of deleting the original end point should be performed. These operations are complex and are liable to make an error.

25           Another problem concerns a change in object frame. When an operator makes the change in position/size of an object frame which lies in one frame image (hereinafter referred to as frame simply), there results in that

the identical object frames in the succeeding frames are also changed to the same position/size as the one object frame, that is, the change is automatically made for object frames for which the operator does not intend to make the  
5 change. Therefore, in the case where an object frame in one frame is changed, it is necessary to pay attention to object frames in the succeeding frames.

In an embodiment of the present invention which will be described in the following, the above problem is  
10 overcome, thereby providing a correcting method in which the simplified operability is attained, an error is hard to generate, and it is easy to find out an error even if the error is generated.

To solve the above problem, an image detecting  
15 method according to one embodiment of the present invention enables the implementation of the change the position of a detection arrow and the change of a detection effectuating domain by interlocking the detection arrow and the detection effectuating domain with each other and moving the  
20 detection arrow. In the case where a detection effectuating domain is to be newly added, there is implemented a construction in which it is possible to perform an operation by clicking the ADD button after the domain to be newly added is designated on a film image beforehand.  
25 Similarly, in the case where a detection effectuating domain is to be deleted or cleared, there is implemented a construction in which it is possible to perform an operation by clicking the CLEAR button after the domain to be

00517173-030000



deleted added is designated on a film image beforehand. In the case where it is desired to move the detection arrow to the end of a film image being displayed so that it is further moved to a zone for which no film image is being  
5 displayed, there is implemented a construction in which frame images are automatically scrolled.

According to an image detecting method according to an embodiment of the present invention in the case where an object frame is changed, the change in object frame is  
10 made for only a selected portion on a film image. Further, object frames outside of a designated area can individually be changed every frame.

Thus, there is realized the image detecting method in which the simplified operability is attained,  
15 an error is hard to generate, and it is easy to find out an error even if the error is generated.

The method for change in detection effectuating domain and object frame according to the present invention will now be described.

20 First, the change in detection effectuating domain (the enlargement/reduction of a domain and the joint of domains) by the dragging of a detection arrow will be described using Fig. 27 which shows a flow chart illustrating an embodiment of a processing performed in the case  
25 where the change in detection effectuating domain is made.

The case of the reduction of a domain will now be described in conjunction with a detection effectuating domain 211 exemplarily shown in Fig. 28.

002020-272560

Fig. 28 is a diagram showing an embodiment of an ID panel when the confirmation or change of the result of detection according to the present invention is made. Reference numeral 2000 denotes an ID panel, numerals 200, 201, 202 and 203 detection arrows, numerals 204, 205, 206, 207 and 208 object frames, numeral 209 a film image, numerals 211 and 212 detection effectuating domains, numerals 213, 214, 215, 216, 217, 218, 219, 220, 221 and 222 frame images arranged in the film image 209 in order along the time axis from the left of the screen, numeral 223 a skip button, numeral 224 a display box, numeral 231 an ADD button, numeral 232 a CLEAR button, numeral 305' an enlarged version of the frame image 213 positioned at the leftmost portion of the film image 209, numeral 306 an enlargement display area where the enlarged image 305' is displayed, numeral 301 an OK button, numeral 302 a CANCEL button, and numeral 313 an OBJECT FRAME ADJUST button.

The detection arrows 200 to 203 displayed on the upper side of the film image 209 are arrows indicating the beginning and end of each detection effectuating domain. The detection arrow 200 or the detection arrow 202 is the head of detection called a begin point. The detection arrow 201 or the detection arrow 203 is the termination of detection called an end point. A domain sandwiched between the detection arrow 200 of the begin point and the detection arrow 201 of the end point is the detection effectuating domain 212, and a domain sandwiched between the detection arrow 202 of the begin point and the detection

005473-030200

arrow 203 of the end point is the detection effectuating domain 211. Each of the object frames 204 to 208 displayed in the frame images belonging to the detection effectuating domain 211 and the detection effectuating domain 212

5 indicates a position at which a character "X" exists in the frame image. The object frame is displayed as the result of character detection.

When the processing shown in Fig. 27 is started, the pointer 810 is moved to the position of the detection  
10 arrow 202 of the begin point in the detection effectuating domain 211 made of an object of change and is then clicked (step 2100).

Next, the mouse pointer 810 is dragged to drag the detection arrow 202 into a desired right/left position  
15 (step 2101).

Thereafter, the check is made of whether or not the mouse pointer 810 being dragged in step 2101 reaches the right/left extreme of the film image 209 (step 2102). When the mouse pointer 810 reaches the right/left extreme  
20 of the film image 209, the flow goes to step 2103. When the case is not so, the flow goes to step 2104.

In step 2103, the film image 209 is subjected to a scroll processing. For example, when the mouse pointer 810 being dragged reaches the right extreme of the film  
25 image 209, frame images positioned on the further right side of the film image 209 are slid leftwards so that they are displayed on the film image 209. Similarly, when the mouse pointer 810 being dragged reaches the left extreme of

00517173-030200



5           The number of frames to be scrolled at once can  
be set in units of the predetermined number of frames (for  
example, in units of one or more frames). A method of  
changing this unit of scroll or the number of frames to be  
scrolled may include, for example, a method in which an  
10 upward/downward arrow on the skip button 223 is attached to  
increase or decrease the number of frames to be skipped  
which is displayed in the display box 224 on the left side  
of the skip button 223 (wherein the attachment of the  
upward arrow causes the increase in number of frames and  
15 the attachment of the downward arrow causes the decrease in  
number of frames), a method in which the number of frames  
is inputted into the display box 224 directly from the  
keyboard, and a method in which the number of frames is  
entered into a configuration file and that numeric value is  
20 written into the memory at the time of start of an applica-  
tion. The configuration file includes various setting  
conditions of the application (for example, the directory  
setting of a destination for output of the file) which are  
designated by the operator beforehand.

25           Next, the judgement is made of whether or not the dragged mouse pointer 810 reaches the position of the detection arrow 203 of the end point paired with the detection arrow 202 (step 2104). When the case is so, the flow

[illegible]

In step 2105, the detection arrow 202 is moved in compliance with the motion of the mouse pointer 810. Then, the flow goes to step 2106.

In step 2107, the flow branches off here to (1) to (5) (steps 2181 to 2185) in accordance with the stop position of the detection arrow 202.

(2) Step 2182: In the case where the begin point  
25 (or the detection arrow 202) lies in the detection  
effectuating domain 211, the extent of detection effectuat-  
ing domain 211 is reduced. For example, provided that the  
detection arrow 202 is dragged rightwards by two frames,

5 of the frame 221 and the display of the object frames 206  
and 207 is extinguished.

ing domain 211 is enlarged. For example, provided that the detection arrow 202 is dragged leftwards by one frame, data of the detection arrow 202 is shifted leftwards by one frame so that data of an object frame is newly added to the data structure. This newly added object frame takes the same size/position as the object frame 206. Thereby, the detection arrow 202 is displayed on the right side of the frame image 217 and the new object frame having the same size/position as the object frame 206 is displayed in the frame 218.

20           (4) Step 1284: In the case where the begin point  
    (or the detection arrow 202) lies in the detection  
    effectuating domain 212 (inclusive of the case where it  
    overlaps the detection arrow 200 or 201), two detection  
    effectuating domains 211 and 212 are joined. Namely, data  
25 of the detection arrow 202 and the detection arrow 201 of  
    the end point is deleted from the data structure and data  
    of three object frames falling between the domains 211 and  
    212 is newly added to the data structure. These newly

added object frames are generated through linear interpolation in position made between the object frames 206 and 205.

(5) Step 1285: In the case where the begin point  
5 (or the detection arrow 202) lies on the further left side than the detection effectuating domain 212, the detection effectuating domain 211 is enlarged so that it is joined with a plurality of domains on the left side thereof (inclusive of the domain 212). The detection arrows and  
10 object frames take the combination of the case of joint and the case of enlargement.

The object frame change based on the linear interpolation will now be described using Fig. 29. Fig. 29 shows an ID panel showing an embodiment of the result of  
15 joint of the detection effectuating domains 211 and 212. In Fig. 29, the same parts as those in Fig. 28 are denoted by the same reference numerals as those used in Fig. 28. Numeral 2001 denotes an ID panel, numeral 200' a detection arrow indicative of a begin point, numeral 203' a detection  
20 arrow indicative of an end point, numeral 209' a film image, numeral 211' a detection effectuating domain, and numerals 251 to 253 object frames.

Fig. 29 shows a state resulting from the leftward movement of the begin point of the detection effectuating  
25 domain 211 (or the detection arrow 202) for the change in domain to overlap the end point of the detection effectuating domain 212 (or the detection arrow 201) (see Fig. 28). The detection arrows 201 and 202 are deleted and the

00517173-030200

detection effectuating domains 211 and 212 are jointed to form a detection effectuating domain 211'.

The new object frames of the frame images 216 to 218 newly added to the detection effectuating domain are  
5 determined from positions obtained by the equi-interval division of lines which connect the apexes of the object frame 205 of the frame image 215 on the left side of the new object frames and the corresponding apexes of the object frame 206 of the frame image 219 on the right side  
10 of the new object frames. Though the connecting lines are depicted in Fig. 29 as dotted lines for the convenience of illustration, those lines are not actually displayed. These linearly interpolated object frames 251 to 253 are displayed. Thus, the frame images 216 to 218 are respec-  
15 tively allotted with the object frames 251 to 253 having their positions and sizes which equally change from that of the object frame 205 to that of the object frame 206.

Though the change in object frame is made by clicking the OBJECT FRAME ADJUST button 313 for the switch-  
20 ing to an object frame change mode, the details thereof will be mentioned later on. When the OK button 301 is clicked after the change in object frame, the ID panel 2001 is closed with the result of change held. On the other hand, when the CANCEL button 302 is clicked, the ID panel  
25 2001 is closed with the result of change cancelled. In the case where the OBJECT FRAME ADJUST button 313 is clicked to switch the ID panel 2001 to the object frame change mode and the OBJECT FRAME ADJUST button 313 is clicked again,

0020200 030200 09517473



the ID panel 2001 returns to the former display mode.

Next, the change in object frame will be described. The change in object frame divides into interpolation change and individual change. The interpolation  
5 change is used when it is desired to correct a plurality of object frames at once (or en bloc). The individual change is used when object frames are to be changed one by one.

First, the description using Figs. 30, 31 and 32 will be made of an embodiment in the case where a plurality  
10 of object frames are interpolated at once. Fig. 30 is a flow chart showing an embodiment of a processing in the case where a plurality of object frames are interpolated at once. Figs. 31 and 32 are diagrams showing an embodiment of an ID panel in the case a plurality of object frames are  
15 interpolated at once. In Figs. 31 and 32, the same parts as those in Fig. 28 are denoted by the same reference numerals as those used in Fig. 28. Numerals 2004 and 2004' denote ID panels, numerals 475 and 475' film images, numeral 473 a detection arrow indicative of a begin point,  
20 numeral 474 a detection arrow indicative of an end point, numerals 453 to 462 frame images, numerals 463 to 470 and 464' to 467' object frames, numeral 471 a detection effectuating domain, and numeral 472 a selected frame area.

When the processing shown in Fig. 30 is started  
25 on the ID panel shown in Fig. 31, the operator selects frame images 454 to 459 (that is, a frame area 472) by use of the mouse pointer 810 (step 2150).

Next, in the case where the OBJECT FRAME ADJUST

005173-030200

In step 2152, the object frame display mode is turned to a change mode. In the object frame change mode, eight square points are added to each of selected object frames 463 to 470, as shown in Fig. 31.

15 In describing the enbloc change made in step  
2154, consider by way of example the case where the  
necessity of making a change in position/size of the object  
frames 463 and 468 is little whereas the position/size of  
the object frame 466 is most different from the pixel  
20 region of a character "X" appearing in the frame image 457.  
In this case, the object frame 466 is subjected to deforma-  
tion or change. The object frame 466 is deformed by drag-  
ging the mouse pointer 810. When the deformation of the  
object frame 466 is completed (or the dragging is stopped),  
25 the object frames 463 to 468 in the selected frame area 472  
are subjected to interpolation change with the object  
frames 463 and 466 taken as origins or reference frames and  
with the object frames 466 and 468 taken as reference

frames, in a manner similar that described in conjunction with Fig. 29. An example of the changed object frames is object frames 464', 465', 466' and 467' displayed in Fig. 32. Dotted lines depicted in Fig. 32 for the convenience of illustration are not actually displayed.

In the case where only one object frame is selected (step 2153), only the selected object frame is subjected to change (step 2156).

When the change in step 2154 or step 2155 is completed, the flow proceeds to step 2156 in which the judgement is made of whether or not the OBJECT FRAME ADJUST button 313 is clicked again. If the button 313 is not clicked, the flow returns to step 2153 to continue the change processing. If the button 313 is clicked, the flow proceeds to step 2157.

In step 2157, the object frame display mode is turned to the former mode so that the change mode is cancelled.

In the case where the OK button 301 is clicked, the ID panel 2004' is closed with the result of change held. On the other hand, in the case where the CANCEL button 302 is attached, the ID panel 2004' is closed with the result of change cancelled.

In the foregoing embodiment, one example of the image detecting method has been described in conjunction with an example in which a character is detected. However, it is self-evident that an object image other than characters can be detected by designating the combination

of specific colors. Further, it is needless to say that the present invention can also be applied in conjunction with a detecting method other than that mentioned above.

Now, the procedure for storing data of the result  
5 of detection of a character always in the information  
region of an M-icon of the lowermost layer of a hierar-  
chical structure will be described in reference to a flow  
chart shown in Fig. 33. In the above-mentioned embodiment  
of the present invention, it has been shown that in the  
10 case where an upper layer of the tree structure, for  
example, the M-icon 1220 "a" (Fig. 8) is attached to  
perform a processing for the detection of the character  
"A", the data of the result of detection of the character  
"A" is stored into data structures corresponding to M-icons  
15 1210 "b", "c" and "d" in the lowermost layer of the tree  
structure. The operation of a processing performed in this  
case will be described referring to the flow chart shown in  
Fig. 33 and data structures shown in Figs. 35 to 41.

In step 8001 for scene number acquisition, a  
20 scene number in a data region 72 of a data structure  
7000(a) (see Fig. 35) of the attached M-icon 1220 "a" is  
acquired. Namely, when an M-icon corresponding to a scene  
is attached in order to detect the character "A", an attach  
structure of the attached M-icon is generated corresponding  
25 to a scene number. For example, assume that an operator  
attaches the M-icons 1031 to 1033 (Fig. 4) in a sequence  
from a smaller number to a larger number. In the case  
where the number of attached M-icons is thus not one but

002020 ECT 7560

plural, a pointer to an attach structure 7000(b) (Fig. 35) of the next attached M-icon is acquired from a data region 71 of the attach structure 7000(a) and a scene number is acquired from a data region 74 of the attach structure  
5 7000(b). Then, a pointer to an attach structure 7000(c) of the next attached M-icon is acquired from a data region 73 of the attach structure 7000(b) and a scene number is acquired from a data region 76 of the attach structure 7000(c). Then, the address of the next attach structure is  
10 acquired from a data region 75 of the attach structure 7000(c). Thus, scene numbers are acquired by the number of attached M-icons.

Next or in step 8002 for scene structure acquisition, there is acquired a scene structure which has the  
15 same scene number as the scene number acquired in step 8001. This scene structure is generated as an editing work is performed to generate a tree structure in the editing area 1010. For example, in the case of the attach structure 7000(a) shown in Fig. 35, a scene structure 7100 shown  
20 in Fig. 36 is found out referring to the scene number stored in the data region 72 of the attach structure 7000(a). In the case of the attach structures 7000(b) and 7000(c), the reference is made to the scene numbers stored in the data regions 74 and 76 of the respective attach  
25 structures.

Next or in step 8003 for display class judgement, a display class is judged from a display class number in the scene structure. For example, in the case where the

00547473-030200

attached M-icon is the M-icon 1220 "a" which represents a scene of the tree structure 1040 having already been edited in the editing area 1010 on the editing window 1000 shown in Fig. 8, a display class number stored in a data region 78 of a scene structure 7100 corresponding to a scene number of that scene is acquired. Namely, data regions 78, 82, 86 and 90 are stored with display class numbers or numeric values each of which indicates a layer in the tree structure for the M-icon corresponding to that scene structure. For example, the display class number equal to "0" indicates the lowermost or first layer, the display class number equal to "1" indicates the second layer, the display class number equal to "2" indicates the third layer, and so forth. Now, the data region 78 is stored with "1" representing the layer of the M-icon 1220 "a" and the data regions 82, 86 and 90 are stored with "0" representing the layer of the M-icons 1210 "b", "c" and "d". In step 8003, the judgement is made of whether or not the scene structure is one of the lowermost layer. If it is the lowermost layer, the flow goes to step 8004. If it is not the lowermost layer, the flow goes to step 8008. The judgement of whether or not the scene structure is one of the lowermost layer, can be made by referring to the data region in which the display class number is stored. Namely, the flow goes to step 8004 if a numeric value stored in the data region for display class number is "0" and step 8008 if it is equal to "1" or larger than that.

In step 8008 for lower layer scene structure

acquisition, there is acquired a scene structure which lies in a layer lower than the tree structure layer of the scene structure acquired in step 8002. For example, provided that a scene structure corresponding to a scene number of the M-icon 1220 "a" shown in Fig. 8 is the scene structure 7100 (Fig. 36), a pointer to (or an address of) a scene structure 7100A corresponding to the M-icon 1210 "b" at the leftmost position of the lower tree layer is stored in a data region 77 of the scene structure 7100. With the reference made to this pointer, the scene structure 7100A can be acquired. Further, the reference is made to a data region 81 of the scene structure 7100A, thereby making it possible to acquire a scene structure 7100B corresponding to the M-icon 1210 "c" on the right side of the M-icon 1210 "b". Similarly, the reference is made to a data region 85 of the scene structure 7100B, thereby making it possible to acquire a scene structure 7100C corresponding to the M-icon 1210 "d" on the right side of the M-icon 1210 "c". If the lowermost scene structure(s) are acquired, the flow returns to step 8003.

In step 8004 for cut structure acquisition, the reference to a cut number stored in any of the data region 84, 88, 92 of the scene structures 7100A, 7100B and 7100C of the lowermost layer (Fig. 36) is made to acquire a cut structure which is storing the same cut number as that cut number. In an example shown in Fig. 36, data regions 83, 87 and 91 of the scene structures 7100A, 7100B and 7100C are stored with scene numbers to which the respective scene

structures belong. Similarly, data regions 84, 88 and 92 of the scene structures 7100A, 7100B and 7100C are stored with cut numbers belonging to the lower layer of the respective scene structures. The reference to a cut number data region of a scene structure having a display class number equal to "0" is made to acquire a cut structure having the same cut number as that cut number. For example, in the case of the scene structure 7100A, the cut structure 7200 (Fig. 37A) is acquired, and in the case of scene structure 7100B, a cut structure 7200A (Fig. 38) is acquired.

Next or in step 8005 for object class structure acquisition, the reference is made to a data region 94 of the cut structure 7200 (Fig. 37A) in which a pointer to object class structure is stored. Thereby, an address for an object class structure 7300P is acquired in which information of the character detection result is stored. Namely, an object class structure for storing information of character search is acquired on the basis of a data region of the cut structure indicating a pointer to object class structure. In the case of the cut structure 7200A shown in Fig. 38, the reference to a data region 95 is made to acquire an address for an object class structure 7300S.

Next or in step 8006 for data storage, each data  
25 of the result of detection is stored into the corresponding  
region of the object class structure 7300P and the succeed-  
ing structures. In other cases, each data of the result of  
character detection is stored into the corresponding region



Next or in step 8007 for cut process completion judgement, the judgement concerning one attached M-icon for cuts in its lowermost layer is made as to whether or not the processing up to the data storage is completed. If the processing is not completed, the flow returns to step 8005. If the processing is completed, the flow proceeds to step 8009.

10           Next or in step 8009 for process completion  
judgement, the judgement concerning all list structures  
7100A to 7100C (Fig. 36) for the scene structures of all  
the attached M-icons is made as to whether or not the  
processing up to the data storage is completed. If the  
15 processing is not completed, the flow returns to step 8002.  
If the processing is completed, the flow is finished.

Next, the procedure for distinctively displaying a domain having already been subjected to character detection processing and a domain having not yet been subjected to character detection processing will be described referring to a flow chart shown in Fig. 34 and the data structures shown in Figs. 35 to 41.

In step 8101 for character search start, an operator attaches the M-icons 1030 to 1032 in the material  
25 area 1020 by use of the mouse pointer 810 and clicks the character detecting button 1051 in the edition function button group 1050, thereby starting a character search.

In step 8102 for data acquisition, the processing

in the flow chart shown in Fig. 33 is performed to acquire data of the cut structures 7200(a) to 7200(c) (Figs. 39 to 41) corresponding to the M-icons 1030 to 1032.

In step 8103 for cut structure selection, one of the cut structures 7200(a) to 7200(c) shown in Figs. 39 to 41 is selected. For example, the cut structure 7200(a) shown in Fig. 39 is selected.

In step 8104 for object class structure selection, there is selected one of object class structures which are under the cut structure selected in step 8103. For example, an object class structure 7300D is selected.

In step 8105 for object name acquisition, an object name in an object name data region of the object class structure selected in step 8104 is acquired. For example, for the object class structure 7300D, an object name "B" in a data region 95 thereof is acquired.

In step 8106 for other object name acquisition, one cut structure other than the cut structure selected in step 8103 is selected and object names in all object class  
20 structures under the selected other cut structure are acquired. For example, for all of object class structures 7300E to 7300H under the cut structure 7200(b) shown in Fig. 40, object names in data regions 96 to 99 thereof are acquired.

25           In step 8107 for object name judgement, the judgement is made of whether or not the same object name as the object name "B" acquired in step 8105 is included in the object names acquired in step 8106. If the same object



steps 8106 to 8109 are completed for all the cut structures. If the case is so, the flow proceeds to step 8111. If the case is not so, the flow returns to step 8106.

In step 8111 for completion 2 judgement, the judgement is made of whether or not the processings of steps 8103 to 8110 are completed for all the cut structures. If the case is not so, the flow returns to step 8103. If the case is so, the processing along the flow chart is completed.

10           Next, the description will be described of the  
data structures of Figs. 35 to 41 used in the present  
invention. In the case where a processing for detection of  
a specified character is performed for frame images in one  
cut, one object class structure is generated for one  
15 character. For example, the zones 604 of the detection  
result display columns 237 and 238 on the IDX panel shown  
in Fig. 1 correspond to the object class structure 7300P  
shown in Fig. 37A and the object class structure 7300Q  
shown in Fig. 37B.

20 By virtue of "POINTER TO NEXT OBJECT CLASS  
STRUCTURE", a list structure for object class structures  
can be formed. For example, the zone 604 of the detection  
result display column 237 on the IDX panel shown in Fig. 1  
shows an object class structure 7300P shown in Fig. 37A and  
25 a pointer to next object class structure field 120 in the  
object class structure 7300P indicates an object class  
structure 7300Q corresponding to the zone 604 of the detec-  
tion result display column 238.

Provided that the zone 604 of the detection result display column 237 on the IDX panel shown in Fig. 1 is the zero-th zone, "0" is stored in a display class number field 121 of the object class structure 7300P shown in Fig. 37A. Also, since the zone 605 of the detection result display column 237 is the 1-st zone, "1" is stored in a display class number field 130 of the object class structure 7300Q shown in Fig. 37B.

By virtue of a pointer to object instance structure 122, it is possible to refer to an object instance structure in which data of one detection effectuating domain is stored. The details of the object instance structure will be described later on.

"ATTACH FLAG" is a flag indicating whether or not a target image on the IDX panel (shown in, for example, Fig. 1) is clicked by the mouse. "ATTACH FLAG" = "1" indicates the presence of attachment and "ATTACH FLAG" = "0" indicates the absence of attachment. For example, in the case where the target image 631 is clicked or attached by the mouse, an attach flag 123 of the object class structure 7300P corresponding to the zone 604 at the head of the detection result display column 237 is turned to "1".

"OBJECT NAME" is a name of a character made an object of character detection processing. For example, the character name 634 "A" on the IDX panel shown in Fig. 1 is stored in an object name 124 of the object class structure 7300P. This name is a name inputted by the user as the object name 547 on the ID panel shown in Fig. 17.

"NUMBER OF COLOR DESIGNATING FRAMES" indicates the number of color designating frames designated for setting a color pattern. For example, since three color designating frames 503, 504 and 505 are set in the enlarged image 502 on the ID panel shown in Fig. 17, a numeric value in a number of color designating frames field 125 of the object class structure 7300P is "3".

00517173.030200  
A "COORDINATE LIST OF FOUR CORNERS OF COLOR DESIGNATING FRAMES" (two-dimensional array) field stores the x- and y-coordinates of four corners of color designating frames on the screen. The x- and y-coordinates are the coordinates on the screen in the lateral and longitudinal directions, respectively. Coordinate sets exist by the number of color designating frames. For example, since three color designating frames are set in the enlarged image 502 on the ID panel shown in Fig. 17, three coordinate sets each having the x- and y-coordinates of four corners of one color designating frame are stored in a coordinate list of four corners of color designating frames field 126 of the object class structure 7300P.

A "LIST OF COLOR DATA IN COLOR DESIGNATING FRAMES" (two-dimensional array) field stores data of designation colors in color designating frames. Color data sets exist by the number of color designating frames. For example, since three color designating frames are set in the enlarged image 502 on the ID panel shown in Fig. 17, three color data sets are stored in a list of color data in color designating frames field 127 of the object class

structure 7300P.

A "POINTER TO OBJECT INFORMATION STRUCTURE" field 128 of the object class structure 7300P stores information for referring to an object information structure in which  
5 information associated with the character made the object of character detection processing (for example, birth date, copyright and so forth) is stored.

In the case where a combine processing is performed on the IDX panel shown in Fig. 1, display class  
10 numbers in object class structures in the same cut made an object of combination are stored in a "COMBINE CLASS LIST" (one-dimensional array) field. For example, in the case where the detection result display columns 237 and 238 are combined, a numeric value in the display class number 121  
15 of the object class structure 7300P and a numeric value in the display class number 130 of the object class structure 7300Q are stored in the combine class list field 129 of the object class structure 7300P.

Next, the object instance structure will be  
20 described. In the case where a processing for detection of a specified character is performed for frame images in one cut, one object instance structure is generated for a domain in which one character exists. For example, the detection effectuating domains 614 in the zones 604 of the  
25 detection result display column 237 on the IDX panel shown in Fig. 1 correspond to object instance structures 7400P, 7400Q and 7400R shown in Figs. 37A, 37B and 37C.

By virtue of "POINTER TO NEXT OBJECT INSTANCE

0051773-030600

5

10

25



5

10

20

(146) of the object instance structure stores information

"DIMENSION OF OBJECT FRAME IN X-DIRECTION"

indicates the length of an object frame on the screen in a lateral direction. For example, the lateral length of the

object frame 561 on the ID panel shown in Fig. 17 is stored in a dimension of object frame in x-direction field 149 of the object position structure 7500P shown in Fig. 37A.

"DIMENSION OF OBJECT FRAME IN Y-DIRECTION"

5 indicates the length of an object frame on the screen in a longitudinal direction. For example, the longitudinal length of the object frame 561 on the ID panel shown in Fig. 17 is stored in a dimension of object frame in y-direction field 150 of the object position structure 7500P shown in Fig. 37A.

"X-COORDINATE OF OBJECT FRAME" indicates the x-coordinate of the left/upper corner of an object frame on the screen. For example, the x-coordinate of the left/upper corner of the object frame 561 on the ID panel shown in Fig. 17 is stored in an x-coordinate of object frame field 151 of the object position structure 7500P shown in Fig. 37A.

"Y-COORDINATE OF OBJECT FRAME" indicates the y-coordinate of the left/upper corner of an object frame on the screen. For example, the y-coordinate of the left/upper corner of the object frame 561 on the ID panel shown in Fig. 17 is stored in a y-coordinate of object frame field 152 of the object position structure 7500P shown in Fig. 37A.

25                    According to the embodiment of the present invention mentioned above, the scroll processing for a film image by the dragging of a detection arrow or the attachment of the film image is possible. Therefore, it is

possible to make the adjustment of a long film image  
without operating a scroll bar.

A second effect of the embodiment of the present  
invention is that it is possible to change only designated  
5 object frames regularly or systematically through inter-  
polation change.

005143.03000